



FORTEC
GROUP

POS-Line 46.0

One look - many functions and options

One partner, unlimited technology solutions

Product Features

POS-Line 46.0

Robust Monitor Series

Variable front options



Monitor description

- Highly variable industry monitor solution
- robust, slim cover offers all options for integration and various applications and various modern business scenarios
- equipped with industrial displays and designed for long term availability
- light and slim design presents a modern small look
- passive cooling allows operating the system under full load even at high ambient temperatures
- VESA Mounting holes for using as an HMI or mounted on a stand
- special wall mount available
- safety glass available



POS-Line IOT

- featuring the Raspberry Pi CM3+ based TFT platform Artista-IoT
- industrial functions like Real-Time-Clock and others
- Basis configuration: CM3+ | 32GB
- Standard configuration: Raspberry Pi®



POS-Line IQ

- two variants of PC configuration
- High performance Intel® Celeron® J3455 processor with 4GB highspeed RAM and an industrial grade SSD with 128 GB memory
- High performance Intel® Core™-i5-7300 (2,6GHz~3,5GHz) processor with integrated graphic card, 8GB DDR4 RAM and 120GB M.2Sata

Panel and Housing

	Measure	Description
Panel Diagonal	[mm] / [Inch]	1168.4/ 46.0
Type		Open -frame monitor (various bezels, true-flat glass and touch solutions are available under options)
Resolution	[Pixel]	1920 x 1080 FHD
Luminance (center)	[cd/m²]	700
Viewing angle (U/ D/ L/ R)	[°]	89/ 89/ 89/ 89
Backlight Number of colors	— [M]	LED 16.7
Active area (H/V)	[mm]	1018.08 x 572.67
Contrast ratio		4000:1
Response time (on/off)	[ms]	6.5
Pixel class		ISO 9241-307 (pixel error class II)
Life time back light until reaching half brightness	[h]	50.000
Continuous operating time	[h] / [d]	24/ 7
Mounting	[mm]	VESA 400 x 400 (M6)
Storage temperature	[°C] / [°F]	-20 ~ 60 / -4 ~ 140
Operating temperature	[°C] / [°F]	0 ~ 40 / 32 ~ 104
Storage/ Operating humidity	[%]	10 ~ 90 (non condensing)
Panel orientation		Landscape and Portrait
Location of connectors and OSD buttons		Landscape: bottom/ Portrait: left (front view)
Housing		Powdered steel sheet, black RAL 9005
IP grade		IP 65 on the front if option TrueFlat glass or TrueFlat touch
Power supply	[V]	AC 110 - 240
Conformity		CE, FCC Class A, EU-RoHS
Packaging		Single packaging single packaging for EURO pallet (max.3 packages p.p.)
Package Contents		Safety instructions

POS-Line 46.0




Monitor with front bezel and with TrueFlat glass

All figures are typical values. The real values of the panel may vary. The optical characteristics are determined after the panel has been „ON“ for approximately 30 minutes at an ambient temperature of 25° C (77° F).

Life time of the backlight is defined as the time to take until the brightness reduces to 50% of its original value.


Video PME - VGA, HDMI, Display Port

POS-Line 46.0



Order number		DS-91-485
Interfaces		1 x VGA, 1 x HDMI, 1 x DisplayPort, 1 x Audio Line-Out, 1 x USB-Remote, 1 x OSD 4 button
Power consumption (typ.)	[Watt]	67
Weight	[kg]	24.5
Dimensions (W x H x D)	[mm]	1078.0 x 633.0 x 110.0
Package contents		SVGA cable


VideoPoster - Network Multimediamplayer



Order number		DS-91-491
Interfaces		1 x LAN, 2 x USB, 1 x HDMI, 1 x Line out, 1 x MicroSD card slot
Power consumption (typ.)	[Watt]	61
Weight	[kg]	24.5
Dimensions (W x H x D)	[mm]	1078.0 x 633.0 x 110.0
Package contents		USB Stick 8 GB

WebPoster M3 - Website Player

POS-Line 46.0





Order number		DS-92-224
Interfaces		1 x LAN, 2 x USB, 1 x HDMI, 1 x Line out, 1 x MicroSD card slot
Raspberry® PI		CM3+, 32 GB
Power consumption (typ.)	[Watt]	61
Weight	[kg]	24.5
Dimensions (W x H x D)	[mm]	1078.0 x 633.0 x 110.0

WebPoster M3 is an industrial FHD network player to show websites. It is a special designed FORTEC Integrated OS for Artista IOT monitors.


Firmware is compatible with touchscreen applications.

IOT - Raspberry® IoT Controller



Order number		DS-91-983
Interfaces		1 x LAN, 2 x USB, 1 x HDMI, 1 x Line out, 1 x MicroSD card slot, 1 x USB-B (only for content updates)
Raspberry® PI		CM3+, 32 GB
Power consumption (typ.)	[Watt]	61
Weight	[kg]	24.5
Dimensions (W x H x D)	[mm]	1078.0 x 633.0 x 110.0


IQ Celeron - PC Intel® Celeron®



POS-Line 46.0

Order number		DS-92-185
Interfaces		2 x Gigabit LAN, 4 x USB 3.0, 1 x HDMI, 1 x RS232/422/485
PC		Intel® Celeron® J3455 (1,5GHz/2,3GHz), RAM: 4 GB DDR3L, Storage: min. 120 GB mSATA
Fan		no
Power consumption (typ.)	[Watt]	72.0
Weight	[kg]	27.3
Dimensions (W x H x D)	[mm]	1078.0 x 633.0 x 110.0

IQ Celeron - PC Intel® Core™ i5



Order number		DS-92-024
Features		Resolution 4K external via DisplayPort supported
Interfaces		2 x DP, 2x LAN, 4x USB 3.0, 1 x Audio, 1 x MIC in
PC		Intel® Core™-i5-7300 U (2.6 GHz), Intel® HD Graphics GT series, RAM: 8GB DDR 4; Storage: 120 GB M.2Sata
Fan		no
Power consumption (typ.)	[Watt]	110
Weight	[kg]	29.0
Dimensions (W x H x D)	[mm]	1078.0 x 633.0 x 110.0

Various accessories are available for POS-Line monitors. All monitors can be customized according to your specific requirements.


Please contact our sales team if you are interested in product modifications or custom designs.

Options

POS-Line 46.0

Bezel

Order number		DS-91-496
Name		Front bezel
Finish		Steel, powdered, black RAL 9005
Can be combined with		Safety glass
Weight	[kg]	1.60
Dimensions of monitor with option (W x H x D)	[mm]	1081.0 x 636.0 x 111.0



Front bezel is a metal bezel for the open frame chassis and VESA mount.

Order number		DS-91-703
Name		TrueFlat bezel with glass
Finish		Sheet steel, RAL 9006 glare (aluminium white), safety glass TSG 4 mm, anti-glare, printed black passepartout RAL 9005
Can be combined with		—
Weight	[kg]	13.40
Dimensions of monitor with option (W x H x D)	[mm]	1109.0 x 663.0 x 116.0



TrueFlat bezel is a metal bezel with round corners, safety glass and passepartout for the open frame chassis.

*Glass will reduce monitor brightness.
** depending on the customer's installation

Options

Order number		DS-90-633	DS-91-500
Name		Safety glass	TrueFlat glass
Finish		Safety glass TSG, 3 mm anti glare	Safety glass TSG, 4 mm anti glare, printed black passepartout RAL 9005
IP grade		—	front IP 65**
Can be combined with		Front bezel	—
Weight	[kg]	6.60	7.50
Dimensions of monitor with option (W x H x D)	[mm]	1078.0 x 663.0 x 115.0	1101.0 x 656.0 x 115.0

*Glass will reduce monitor brightness.

** depending on the customer's installation


POS-Line 46.0

Glass*



Safety glass is an accessory for the open frame chassis, in the picture with front bezel. It covers and protects the TFT-panel.

TrueFlat glass is a safety glass with round corners and passepartout for open frame chassis.




Accessories

Order number		DS-92-033
Name		PC Box extern IQ Core™-i5 DFI KU173
Description		PC module for external mounting
Interfaces		2 x DP, 2x LAN, 4x USB 3.0, 1 x Audio, 1 x MIC in
PC		Intel® Core™-i5- 7300 U(2.6 GHz), Intel® HD Graphics GT series, RAM: 8GB DDR 4 Storage: min. 120 GB M.2Sata
Available for controller		Video PME
Fan		no
Weight	[kg]	2.60
Dimensions of monitor with option (W x H x D)	[mm]	240 x 257 x 48.5
Power supply		DS-91-945 for operate the PC box as stand alone device without display for maintenance, 12V/ 60 W

Order number		DS-92-135
Name		PC-Box IQ Celeron®
Description		PC module for external mounting
Interfaces		2 x Gigabit LAN, 4 x USB 3.0, 2 x USB 2.0, 1 x HDMI, 1 x RS232/422/485
PC		Intel® Celeron® J3455 (1,5GHz/2,3GHz), RAM: 4 GB DDR3L Storage: min. 120 GB mSATA
Available for controller		Video PME
Fan		no
Weight	[kg]	1.70
Dimensions of monitor with option (W x H x D)	[mm]	240 x 260 x 50
Power supply		DS-91-945 for operate the PC box as stand alone device without display for maintenance, 12V/ 60 W

POS-Line 46.0

External PC



Optional removable PC box with Core-i5 CPU. The PC box can be removed without taking the display down from the wall.



Optional removable PC box with Intel Celeron CPU. The PC box can be removed without taking the display down from the wall.

Accessories

POS-Line 46.0

Electronic

Mount

Cable

Product	Order no.	Product description
Remote control	DS-91-621	OSD remote controll for all displays of the Video PME series
Ambient Light Sensor	DS-91-963	ALS for all displays of the Video PME and VideoPoster, can be combined with front bezel and safety glass
SSD Extension Celeron®	DS-91-997	Extension for SSD MSATA up to 240 GB for IQ Celeron®
RAM Extension Celeron®	DS-91-975	Extension for RAM up to 8 GB for IQ Celeron®
SSD Extension Core™-i	DS-92-027	Extension for SSD M.2 up to 240 GB for IQ Core™-i5
RAM Extension Core™-i	DS-92-028	Extension for RAM up to 16 GB for IQ Core-i5

Product	Order no.	Product description
Wall mount	DS-91-540	Inclinable wall mount for all displays from 31.5" up to 46.0"
Wall mount	DS-91-100	Titling wall mount from 31.5" to 46.0", VESA 600 x 450, only for Landscape
Wall mount	DS-91-101	Titling wall mount from 46.0" to 64.5", VESA 800 x 450, only for Landscape
Wall mount PC	DS-92-094	Wall mount for external PC-Box
Cable cover for connctetors	DS-91-723	Cover for the cable connectors to prevent unauthorized persons from removing or plugging cables. For all POS-Line displays of the PME series from 31.5" up to 46.0"
Cable cover for connctetors	DS-91-578	Cover for the cable connectors to prevent unauthorized persons from removing or plugging cables. For all POS-Line displays of the IQ Series from 31.5" up to 46.0". Also suited for optional PC boxes DS-92-033 and DS-92-135.
Cable cover for connctetors	DS-91-922	Cable cover. Only available in combination with covers DS-91-723 and DS-91-578.

Product	Order no.	Product description
Cable DP for PC box	KA-40-115	DP cable for connection PC 0.5 m
Display Port cable	KA-40-105	Cable Display Port 1.2 4k male/ male 2m
Power cord UK	DB-07-226	Power cord UK 1,8 m
Power cord USA	DB-07-238	Power cord USA 1,8 m

Accessories

POS-Line 46.0

Software

Product	Order no.	Product description
WIN 10 IOT Celeron®	DS-60-899	Embedded operation system 2019 LTSC Entry
WIN 10 IOT Core™-i5	DS-60-898	Embedded operation system 2019 LTSC Value
IoT Raspberry Pi OS	DS-60-859	for POS-Line IoT

Windows 10 IoT Enterprise is a full version of Windows 10 that provides enterprise manageability and security for embedded devices and IoT solutions such as medical devices, industrial automation, measurement systems, and more. It's a binary equivalent of Windows 10 Enterprise, so you can use the same familiar development and management tools as you would on client PCs and laptops. The embedded version of Windows 10 IoT Enterprise is supported by Microsoft for at least 10 years.

The information contained in this document has been carefully researched and is, to the best of our knowledge, accurate. However, we assume no liability for any product failures or damages, immediate or consequential, resulting from the use of the information provided herein. Our products are not intended for use in systems in which failures of product could result in personal injury. All trademarks mentioned herein are property of their respective owners. | Copyright 2024 FORTEC Integrated GmbH. All specifications are subject to change without notice.

Unser Unternehmensnetzwerk unterstützt Sie weltweit mit Niederlassungen in Deutschland, Österreich, der Schweiz, Großbritannien und den USA. Für weitere Informationen kontaktieren Sie bitte:

CONTACT

FORTEC GROUP

FORTEC Elektronik AG | Augsburg Str. 2b | 82110 Germering
+49 89 894450-0
info@fortecag.de | www.fortecag.de

FORTEC INTEGRATED

FORTEC Integrated GmbH | Augsburg Str. 2b | 82110 Germering
+49 89 894363-0
info@fortec-integrated.de | www.fortec-integrated.de

FORTEC POWER

AUTRONIC Steuer und Regeltechnik GmbH | Siemensstraße 17 |
74343 Sachsenheim
+49 7147 24-0
vertrieb@autronic.de | www.autronic.de

FORTEC Power GmbH | Lise-Meitner-Straße 3 | 64560 Riedstadt
+49 6158 8285-0
weborder@fortec-power.de | www.fortec-power.de

FORTEC CZECH REPUBLIC

FORTEC Czech Republic s.r.o. | Přátelství 275 | 330 02 Dýšina
+42 0377 845878
alltronic@alltronic-sro.cz | www.alltronic-sro.cz

FORTEC SWITZERLAND

FORTEC Switzerland AG | Bahnhofstraße 3 | 5436 Würenlos
+41 44 7446111
info@fortec.ch | www.fortec.ch

FORTEC UNITED KINGDOM

FORTEC Technology UK Ltd. | Osprey House | 1 Osprey Court
Hinchingsbrooke Business Park | Huntingdon | Cambridgeshire | PE29 6FN
+44 1480 411600
info@fortec.uk | www.fortec.uk



Apollo Display Technologies, Corp. | 87 Raynor Avenue Unit 1 | Ronkonkoma
NY | 11779
+1 631 5804360
info@apollodisplays.com | www.apollodisplays.com